FOR A GOOD REASON GRUNDIG

MICRO SYSTEMS		OVATION 2i CDS 9000 WEB	OVATION 3 CDS 8120 ENC	OVATION 3 CDS 8000 iP	OVATION 2 CDS 7000 DEC	OVATION CDS 6680 USB
SPECIAL FEATURES						
Internet radio via v-tuner		•	–	–	–	–
Audio streaming (UPnP client)		•	–	–	–	–
iPhone/iPod docking station		–	–	•/•	–	–
USB / SD(HC) recording		–	•	•	–	–
AMPLIFIER UNIT						
PMPO	W	90	500	160	90	80
Music / nominal output	W	2 x 6 / 4 / 1 x 11/7	2 x 120 / 2 x 100 (4 ohms)	2 x 10/7 / 1 x 20/15	2 x 6 / 4 / 1 x 11/7	2 x 5 / 3 / 1 x 10/6
Dynamic Bass Boost / Ultra Bass System		•/–	•/–	•/–	•/–	•/–
Digital Sound Control		•	•	•	•	•
Preprogrammed EQ settings		5	5	5	5	5
Volume control digital		•	•	•	•	•
Wake-up function / Sleep function		•/•	•/•	•/•	•/•	•/•
TUNER UNIT						
Ranges		FM	FM	FM	FM, AM (MW)	FM, AM (MW)
PLL frequency synthesizer / Station memory		•/40	•/40	•/40	•/40	•/40
Radio Data System RDS / RDS radiotext		•/•	•/•	•/•	•/•	•/–
Programme type evaluation PTY		•	•	•	•	•
CD UNIT						
D/A converter	bit	1	1	1	1	1
Title memory		40	60	60	60	60
Shuffle (random play)		•	•	•	•	•
Can read CD-R / CD-RW		•/•	•/•	•/•	•/•	•/•
MP3 format		MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz
WMA		•	•	•	•	•
Maximum folders / Maximum files		512	99 / 999	99 / 999	512	512
Data rate system		32 - 320 kbps, variable	32 - 320 kbps, variable	32 - 320 kbps, variable	32 - 320 kbps, variable	32 - 320 kbps, variable
ISO 9660 level 1 compatible		•	•	•	•	•
CASSETTE UNIT						
Automatic tone control		–	–	–	–	–
CD copy function		–	–	–	–	–
Transmission range	Hz	–	–	–	–	–
CONNECTIONS						
WLAN		802.11b/g	–	–	–	–
LAN		RJ45 10/100 MBit	–	–	–	–
USB		•	•	•	•	•
SD, MMC slot		–	• (+ SDHC)	• (+ SDHC)	–	•
Line-, Aux in		•	•	•	•	•
75 ohms antenna coax.		•	•	•	•	•
Stereo headphones (3.5 mm)		•	•	•	•	•
Remote control / HiFi speakers (included)		•/ Magic Fidelity System	•/–	•/ Magic Fidelity System	•/ Magic Fidelity System	•/ Magic Fidelity System
MAINS UNIT						
Mains supply, mains frequency	V~, Hz	230, 50/60	230, 50/60	230, 50/60	230, 50/60	230, 50/60
Power consumption max. / stand-by	approx. W	28 / <6	340 / <1	23 / <1	39 / <2	35 / <2
DIMENSIONS						
Dimensions tower (W x H x D)	approx. cm	29.5 x 30 x 12.7	40 x 28 x 15.7	40 x 28 x 15.7	29.5 x 30 x 12.7	31 x 18 x 19
Dimensions speakers (W x H x D)	approx. cm	built-in	not included in delivery	built-in	built-in	built-in

Technical data supplied without liability.

FOR A GOOD
REASON
GRUNDIG

MICRO SYSTEMS		UMS 5810 WEB	UMS 4950 iP	UMS 4910 DEC	UMS 2020
SPECIAL FEATURES					
Internet radio via v-tuner		•	–	–	–
Audio streaming (UPnP client)		•	–	–	–
iPhone/iPod docking station		–	•/•	–	–
USB / SD(HC) recording		–	•	–	–
AMPLIFIER UNIT					
PMPO	W	360	65	65	32
Music / nominal output	W	2 x 45 / 30 (4 ohms)	2 x 8 / 5 (8 ohms)	2 x 8 / 5 (8 ohms)	2 x 4 / 2 (8 ohms)
Dynamic Bass Boost / Ultra Bass System		•/–	•/–	•/–	–/•
Digital Sound Control		•	•	•	•
Preprogrammed EQ settings		5	5	5	4
Volume control digital		•	•	•	•
Wake-up function / Sleep function		•/•	•/•	•/•	•/•
TUNER UNIT					
Ranges		FM, AM (MW)	FM	FM	FM, AM (MW)
PLL frequency synthesizer / Station memory		•/40	•/40	•/40	•/40
Radio Data System RDS / RDS radiotext		•/•	•/•	•/•	•/•
Programme type evaluation PTY		•	•	•	•
CD UNIT					
D/A converter	bit	16	1	1	1
Title memory		40	20	20	20
Shuffle (random play)		•	•	•	–
Can read CD-R / CD-RW		•/•	•/•	•/•	•/•
MP3 format		MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz	MPEG 1 layer 3, 44.1 kHz
WMA		•	•	•	•
Maximum folders / Maximum files		256 / 511	99 / 999	99 / 999	99 / 999
Data rate system		32 - 320 kbps, variable	32 - 320 kbps, variable	32 - 320 kbps, variable	32 - 320 kbps, variable
ISO 9660 level 1 compatible		•	•	•	•
CASSETTE UNIT					
Automatic tone control		–	–	–	•
CD copy function		–	–	–	•
Transmission range	Hz	–	–	–	125 - 8,000
CONNECTIONS					
WLAN		802.11b/g	–	–	–
LAN		RJ45 10/100 MBit	–	–	–
USB		•	•	•	•
SD, MMC slot		•	• (+ SDHC)	• (+ SDHC)	• (+ SDHC)
Line-, Aux in		•	•	•	•
75 ohms antenna coax.		•	•	•	–
Stereo headphones (3.5 mm)		•	•	•	•
Remote control / HiFi speakers (included)		•/ 2-way bass reflex	•/ 2-way bass reflex	•/ 2-way bass reflex	•/ bass reflex
MAINS UNIT					
Mains supply, mains frequency	V~, Hz	230, 50/60	230, 50/60	230, 50/60	230, 50/60
Power consumption max. / stand-by	approx. W	100 / <1	33 / <1	33 / <1	15 / <2
DIMENSIONS					
Dimensions tower (W x H x D)	approx. cm	16 x 25.5 x 26	15 x 23.7 x 23.5	15 x 23.7 x 23.5	15 x 23.2 x 20.3
Dimensions speakers (W x H x D)	approx. cm	16 x 25.5 x 24	14 x 23.7 x 20.5	14 x 23.7 x 20.5	15 x 23.2 x 20.3

Technical data supplied without liability.